

Boomlift / Manlift

Used Boom Lift San Diego - One of the commonest types of industrial equipment and aerial equipment is the boom lift. Commonly known as aerial work platforms, mobile elevating work platforms, cherry pickers, aerial devices and elevating work platforms, it was engineered to complete work at higher locations more efficient and easier. There are many places to find boom lifts at work including warehouses, contractors, various companies and in retail stores. Keeping workers safe as they access conditions in a higher altitude is priceless. There are numerous models of boom lifts available in the industry. Many models are capable of being operated by a single individual. Boom lifts are beloved in the agricultural and orchard industries, used to harvest fruit without requiring a separate ladder, they keep workers much safer since there is not climbing or bucket balancing involved. Ladders need to be secured on solid, even ground in order to be safely accessible, making them hard to rely on in a natural orchard setting. Boom lifts make it much easier to reach high tree tops for collecting fruit. Gaining Access Over Obstacles Some boom lift models can move up and over obstacles, making them ideal for working over top of items safely and efficiently. Boom lifts can reach items even when it is impossible to move the machine right underneath the area you are working in, making it possible to fix overhead cables within telephone line and pole installation, window cleaning applications and similar circumstances. Articulated boom lifts are comprised of many joints that allow the machine to bend under or over obstacles. The articulated boom sections can move independently to grant operators access to many locations. This equipment is popular in narrow storage locations and hallways thanks to its' tight turning radius. There are dual-fuel models that can work inside and outside; diesel is best utilized outside while interior locations rely on electric models. Articulating Boom Lifts Articulated boom lifts are commonly found on construction sites and used in maintenance applications. Articulated boom lifts are utilized commonly for working on overhead power lines and wires. Certain models are outfitted with water cannons to be used in firefighting applications. Maximum reach can be attained with telescoping boom sections on certain models. Certain articulating boom lifts can extend an additional six feet in any direction thanks to the additional jib in their design. These boom lifts go by the nickname of "spiders," since their legs can support the entire machine on steep or difficult terrain. Smaller units called interior articulating boom lifts are capable of fitting through doorways, making them valuable in retail, warehousing and storage facilities. Interior models are typically electric boom lifts due to their lack of dangerous carbon monoxide exhaust and quieter features. Telescopic Boom Lifts Designed otherwise, telescopic boom lift models bend differently from articulating boom lifts. These models extend upwards and outwards, relying on hydraulics that extend and retract. The worker who is in the platform has the controls to extend the lift and is able to operate without a second worker. Certain larger and taller models feature a jib located close to the top similar to an articulating boom lift model. Some models of boom lifts can achieve a reach of more than 180 feet. In less than a minute, some models can reach their full extended height since these machines are so stable and reliable. Adjustable speed, along with varying weight range capacities from 500 to 1000 lbs. are available in dual-fuel and diesel options. Available in 4WD and the ability to fit through small spaces. In terms of combining height and reach, telescopic boom lifts are your best bet. Jib Boom lifts that have an extension between the platform and the end of the primary boom are called the jib. Certain models offer an additional articulation point or hinge that allows the platform to travel horizontally and vertically. Jibs are an option on many telescoping and articulating boom lifts. Articulating boom lifts have a joint found approximately halfway between the platform and the wheels to allow it to reach over obstacles. The operator can lower the machine again afterward if required. Genie Articulating Boom Lifts A popular type of articulating boom lift manufactured on the market is the Genie Z-boom Model. This unit offers exceptional versatility for accessing difficult to reach locations with the capacity to lift up, over and out with precision. The first Genie Z-30/20 articulating Z-boom model was launched in 1985. Thanks to their "up an over" abilities, they have gained the

ultimate popularity that continues today. Proper Safety Measures Safety is the utmost priority when operating any kind of boom lift. Safety hazards must be advertised to everyone who is working in the area for best practices. Safe operation of the machine and personal safety must be paramount. Before starting the boom lift, it is paramount that the proper safety gear and communication is in place. Prior to operating, ensure there are no open flames, combustible or flammable items, lit cigarettes, battery gases or engine fuels present. It is important to have an accessible, securely mounted and visible fire extinguisher mounted within the operators' reach. Keep work surfaces and charging stations clean and free from clutter or tools that could puncture the tires or damage the machine or its components. Daily Maintenance Daily maintenance includes a visual inspection and consulting the maintenance manual to ensure the machine is up to date and will operate safely. Stabilizing the weight is accomplished supportive devices to lift and distribute the load. Fasteners, straps and chains must be regularly checked to make sure they are safe working order. Single-use fasteners and components must not be reused as they may fail and become extremely dangerous. Discarded solvents and oils must be disposed of safely and in an approved container to prevent environmental contamination. Workbenches and workshop or garage areas need to have adequate lighting and ventilation. Typically the wide umbrella of maintenance is distinguished by subsections such as Commissioning and Programmed Maintenance Intervals, Annual Maintenance, and Quarterly Maintenance. Maintenance Inspection Report Key components of the boom lift are divided up to categorize the inspection process. Some of the maintenance categories for the boom lift include the Engine, Platform, Controls and Function, Turntable, Booms and Drive Chassis. Improperly conducting maintenance can lead to unsafe working conditions, damaged components, reduced performance and ultimately downtime. The maintenance inspection report extend the performance and service life of the machine and needs to be accurately maintained to ensure the machine is safe to run and that the machine is capable of performing properly. A list of single maintenance procedures that need to be conducted at 50-hour and 150-hour intervals is known as commissioning. There is quarterly and annual maintenance protocol that is conducted once or many times during the year. Maintenance procedures are based on the operating hours of the boom lift and programmed maintenance may be conducted during pre-delivery machine preparation. Prior to operating your equipment, check your maintenance manual to make sure all of the fluid levels, oil changes, battery life and maintenance are up to date.